

From pasture to market, and everything in between

Standard Features

- 16', 20', 24', & 28' lengths
- 5', 6', 6'6", and 6'8" widths
- 6'6" bow height
- bartop
- 3 plank spaced sides
- 3/16" or 7 gauge steel body and brush fender material
- schedule 40 11/4" bow pipes on 4' centers
- 4" channel crossmembers on 4' centers
- 2"x 2"x 3/16" angle iron floor runners full length of trailer
- double T braces
- 8" channel iron neck
- adjustable 2-5/16" (25K) ball coupler (hitch)
- 3/16" formed neck gussets
- schedule 40 heavy duty vertical pipe gates with one piece outer bow frame
- split tailgate
- 1 crossgate (16' & 20' lengths)
- · 2 crossgates (24' & 28' lengths)
- sandblasted, primed with rust inhibitive primer and painted with 2 coats paint

- · last 8' open top
- 2-dally balls
- 2"x 6" & 2"x 8" treated lumber floor
- 1 spring loaded drop leg jack
- electric brakes (all axles)
- · cambered spring axles
- 6K, 7K, 7.2K, and 8K axles available
- 8 hole 16" wheels
- 235 85 R16 radial tires
- stainless steel center caps
- spare tire, wheel and rack
- saftey chains
- lights meet U.S.DOT required specifications
- 3 light LED bars on front and rear
- conspicuity (reflective) tape
- 4"x 2" rectangle tube bumper
- 5 year limited warranty

MBJ Trailers

11840 Hyw 60 South | Wharton, Texas 77488

Phone: 979-578-8771 Fax: 979-532-4977