Steel Stock Trailers

Standard Features

- 16’, 20’, 24’, 28’, 32’, 36’, & 40’ lengths
- 5’, 6’, 6’6”, 6’8” 7’, & 7’6” widths
- 6’6” bow height
- bartop
- 3 plank spaced sides
- 3/16’ or 7 gauge steel body and brush fender
- schedule 40 1¼” bow pipes on 4’ centers
- 4” channel cross members on 4’ centers
- 2” x 2” x 3/16” angle iron floor runners full length of trailer
- double T braces
- 3/16” formed neck gusset
- 8” channel iron neck up to 28’ and 10” channel iron neck on 32’ and up
- adjustable 2-5/16” (25K) ball coupler (hitch)
- schedule 40 heavy duty vertical pipe gates with one piece outer bow frame
- split tailgate
- 1 crossgate (16’ & 20’ lengths)
- 2 crossgates (24’, 28’ & 32’ lengths)
- 3 crossgates (36’ & 40’ lengths)
- sandblasted, primed with rust inhibitive primer and painted with 2 coats of paint
- 2” x 6” and/or 2” x 8” treated pine floor
- 1 spring loaded drop leg jack
- electric brakes (all axles)
- cambered spring axles
- 6K, 7K, 7.2K, 8K, and 10K axles available
- 8 hole 16” wheels
- 235 85 R16 radial tires
- center caps
- spare tire and rack
- safety chains
- lights meet U.S.DOT required specifications
- conspicuity (reflective) tape
- 4” x 2” rectangle tube bumper
- 3-light LED bars on front and rear
- 5 year limited warranty

MBJ Trailers

11840 Hyw 60 South | Wharton, Texas 77488

Phone: 979-578-8771

Fax: 979-532-4977